

AMENDMENTS TO THE CLAIMS

A complete listing of the claims is provided as follows:

1. (Currently Amended) A method for sensing a disturbance in a transmission path of a converging ultrasound energy beam transmitted by a transducer in a focused ultrasound system, the method comprising:
 - transmitting a burst of ultrasound energy from the transducer, along the transmission path, to a focal zone;
 - detecting whether a reflected portion of the ultrasound energy burst is received at the transducer within a certain time period following transmission of the burst, wherein receipt within the time period indicates the reflected portion was reflected by a disturbance located in the transmission path proximal of the focal zone; and
 - if the reflected portion is received at the transducer within [[a]] the certain time period, [[following transmission of the burst, then]] analyzing the received reflected portion to [[detect a]] determine one or more characteristics of the disturbance [[in the transmission path between the transducer and the focal zone]].
2. (Original) The method of claim 1, wherein analyzing the received reflected portion comprises determining a delay time from when the burst was transmitted to when the received reflected portion was received at the transducer.
3. (Currently Amended) The method of claim 2, wherein [[analyzing the received reflected portion]] one of the one or more characteristics comprises [[determining]] a distance from the transducer to the [[a]] disturbance [[reflecting the respective portion back to the transducer]] based on the [[a]] determined delay time.
4. (Currently Amended) The method of claim 2, wherein [[analyzing the received reflected portion]] one of the one or more characteristics comprises [[determining]] a location of the [[a]] disturbance [[determined, reflecting the respective portion back to the

transducer]] based, at least in part, on the [[a]] determined delay time [[of the reflected portion]].

5. (Original) The method of claim 1, wherein analyzing the received reflected portion comprises determining an intensity of the reflected portion.

6. (Currently Amended) The method of claim 5, wherein at least one of the one or more [[analyzing the received reflected portion comprises determining a]] characteristics is determined [[of a disturbance reflecting the respective portion back to the transducer]] based, at least in part, on the [[a]] determined intensity of the reflected portion.

7. (Original) The method of claim 1, wherein the transducer comprises an array of transducer elements, and wherein transmitting a burst of ultrasound energy from the transducer comprises simultaneously transmitting a burst of ultrasound energy from each of the transducer elements.

8. (Original) The method of claim 6, wherein detecting whether a reflected portion of the ultrasound energy burst is received at the transducer comprises sampling each transducer element after simultaneously transmitting a burst of ultrasound energy from each of the transducer elements to determine which, if any, transducer element receives a reflected portion of the burst.

9. (Original) The method of claim 8, further comprising repeating each step one or more times.

10. (Original) The method of claim 8, wherein analyzing the received reflected portion comprises determining a delay time from when the burst was transmitted to when the reflected portion was received at the transducer for each transducer element that receives a reflected portion of the ultrasound energy burst.

11. (Original) The method of claim 1, further comprising storing data related to a received reflected portion of the ultrasound energy burst.

12. (Currently Amended) The method of claim 11, wherein the stored data related to a received reflected portion of the ultrasound energy burst comprises at least one of a group consisting of a determined delay time from when the burst was transmitted to when the received reflected portion was received at the transducer, a determined distance from the transducer to a disturbance reflecting the respective portion back to the transducer, and a determined intensity of the reflected portion.

13. (Original) The method of claim 1, further comprising displaying information related to a received reflected portion of the ultrasound energy burst.

14. (Currently Amended) The method of claim 13, wherein displaying information [[related to a received reflected portion of the ultrasound energy burst]] comprises overlaying data related to a received reflected portion on an image of the transducer in order to indicate a portion of the transducer which received the reflection.

15. (Original) The method of claim 14, further comprising displaying the information as a single trace of data.

16. (Currently Amended) The method of claim 1, further comprising switching a transducer used to transmit the burst of ultrasound energy from continuous wave operation to burst operation before transmitting the burst of ultrasound energy, and thereafter switching [[to]] the transducer from burst operation to continuous wave operation after a time period required for the burst of ultrasound energy to travel from the transducer to the [[a]] focal zone [[spot of the transducer]] and back to the transducer.

17. (Currently Amended) A focused ultrasound system comprising:
a transducer configured to transmit a burst of ultrasound energy in a converging transmission path to a focal zone, and to received reflected portions of the ultrasound energy burst,
the system configured to analyze reflected portions of an ultrasound energy burst received by the transducer within a certain time period following

transmission of the respective burst, wherein receipt within the time period indicates the reflected portion was reflected by [[and to detect]] a disturbance located in the transmission path proximal of [[between the transducer and]] the focal zone [[based on the analyzed portions]].

18. (Original) The focused ultrasound system of claim 17, wherein analysis of the received reflected portion comprises determining a delay time from when the burst was transmitted to when the received reflected portion was received at the transducer.

19. (Currently Amended) The focused ultrasound system of claim 18, wherein analysis of the received reflected portion comprises determining a distance from the transducer to the [[a]] disturbance [[reflecting the respective portion back to the transducer]] based, at least in part, on the [[a]] determined delay time.

20. (Currently Amended) The focused ultrasound system of claim 18, wherein analysis of the received reflected portion comprises determining a location of the [[a]] disturbance [[reflecting the respective portion back to the transducer]] based, at least in part, on the [[a]] determined delay time of the reflected portion.

21. (Original) The focused system of claim 17, wherein analysis of the received reflected portion comprises determining an intensity of the reflected portion.

22. (Currently Amended) The focused ultrasound system of claim 21, wherein analysis of the received reflected portion comprises determining a characteristic of the [[a]] disturbance [[reflecting the respective portion back to the transducer]] based, at least in part, on the [[a]] determined intensity of the reflected portion.

23. (Currently Amended) The focused ultrasound system of claim 17, wherein the transducer comprises an array of transducer elements, and wherein the system [[transducer]] is further configured to simultaneously transmit a burst of ultrasound energy from each transducer array element.

24. (Original) The focused ultrasound system of claim 23, further configured to sample each of the transducer array elements to determine which if any received a reflection of the ultrasound energy from the disturbance in the path of the ultrasound energy.
25. (Currently Amended) The focused ultrasound system of claim 24, [[wherein the transducer is]] further configured to transmit a series of ultrasound energy bursts from each transducer array element.
26. (Original) The focused ultrasound system of claim 25, further configured to serially sample each of the transducer array elements after each transmission in the series of transmitted ultrasound energy bursts.
27. (Original) The focused ultrasound system of claim 24, further configured to determine a delay from transmission of a burst of ultrasound energy to reception of a reflection for each transducer element that receives a reflection.
28. (Currently Amended) The focused ultrasound system of claim 20, further comprising a memory, wherein the system is configured to store information related to the received reflection in the memory.
29. (Original) The focused ultrasound system of claim 20, further comprising a display, and wherein the system is configured to display information related to the received reflection on the display.
30. (Original) The focused ultrasound system of claim 29, further configured to display the information related to the received reflection overlaid on an image of the transducer.
31. (Currently Amended) The focused ultrasound system of claim 29, further configured to display the information related to the received reflection as [[is]] a single trace.

32. (Original) The focused ultrasound system of claim 29, further configured to generate a 3D reconstruction of the disturbance, and to display the 3D reconstruction on the display.
33. (Original) The focused ultrasound system of claim 17, further comprising a controller communicatively coupled with the transducer, the controller configured to control the operation of the transducer.
34. (Currently Amended) The focused ultrasound system of claim 33, wherein the controller is configured to switch the transducer from continuous wave operation to burst operation before the transmitter transmits the burst of ultrasound energy and to switch the transducer back to continuous wave operation after a time period required for the ultrasound energy to travel from the transducer to a focal spot of the transducer and back to the transducer again.
35. (Currently Amended) The focused ultrasound system of claim 17, further comprising a processor, wherein the processor [[is configured to]] determines the delay and the range.
36. (Currently Amended) The focused ultrasound system of claim 35, wherein the processor [[is further configured to]] determines the phase and amplitude of the received reflection.
37. (Currently Amended) The focused ultrasound system of claim 36, wherein the transducer comprises an array of transducer elements, and wherein the processor [[is further configured to]] determines the phase and amplitude of the received reflection relative to each transducer array element.
38. (Currently Amended) The focused ultrasound system of claim 35, [[wherein the processor is]] further configured to analyze the integrity of the burst of ultrasound energy transmission path.

